

87654321

1. ALL RESISTANCE VALUES ARE IN OHMS, 0.1 WATT +/- 5%.

2. ALL CAPACITANCE VALUES ARE IN MICROFARADS.

3. ALL CRYSTALS & OSCILLATOR VALUES ARE IN HERTZ.

REV

ZONE

ECN

DESCRIPTION OF CHANGE

CK APPD

DATE

ENG APPD

DATE

?

?

SCHEM, LIO/AUDIO , MacBook Pro 15"

9/22/06

PDF PAGE	CSA PAGE	CONTENTS	SYNC MASTER	DATE
1	1	Table of Contents		
2	2	Block Diagram		
3	4	BOM Configuration	(Master)	(Master)
4	6	Aliases	(Master)	(Master)
5	51	Left USB Port	(Master)	(Master)
6	53	ExpressCard Connector	(Master)	(Master)
7	54	PCI-E MiniCard Connector	(Master)	(Master)
8	55	MLB I/O Board Connector	(Master)	(Master)
9	68	AUDIO: CODEC	AUDIO_MBP15	08/15/2006
10	72	AUDIO:SPEAKER AMP	AUDIO_MBP15	08/15/2006
11	73	AUDIO: JACKS	AUDIO_MBP15	08/15/2006
12	74	AUDIO: JACK TRANSLATORS	AUDIO_MBP15	08/15/2006
13	78	3.3V Supply	(Master)	(Master)
14	82	DC-In & Battery Connectors	(Master)	(Master)
15	83	PBus Supply & Batt. Charger	(Master)	(Master)
16	84	Current & Thermal Sensors	(Master)	(Master)
17	85	Cross Reference Page		
18	86	Cross Reference Page		

PART#	QTY	DESCRIPTION	REFERENCE DESIGNATOR(S)	CRITICAL	BOM OPTION
051-7146	1	SCHEM, LIO/AUDIO, MacBook Pro 15	SCH1	CRITICAL	
820-2055	1	PCBF, LIO/AUDIO, MacBook Pro 15	PCB1	CRITICAL	

DIMENSIONS ARE IN MILLIMETERS

XX ± _____

X.XX ± _____

X.XXX ± _____

ANGLES ± _____

DO NOT SCALE DRAWING



THIRD ANGLE PROJECTION

METRIC

DRAFTER	/	DESIGN CK	/
ENG APPD	/	MFG APPD	/
QA APPD	/	DESIGNER	/
RELEASE	/	SCALE	NONE
MATERIAL/FINISH NOTED AS APPLICABLE		SIZE	

